

(19)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: **08274066 A**

(43) Date of publication of application: **18.10.96**

(51) Int. Cl

H01L 21/3065

H01L 21/28

H01L 21/306

H01L 21/768

(21) Application number: **07071088**

(71) Applicant: **MATSUSHITA ELECTRIC WORKS LTD**

(22) Date of filing: **29.03.95**

(72) Inventor: **OKA NAOMASA**

(54) FORMATION OF CONTACT WINDOW

(57) Abstract:

PURPOSE: To contrive to improve the reliability of a metal wiring which is formed in a contact window.

CONSTITUTION: A BPSG film 9 formed on a semiconductor substrate 5 by a CVD method is heat-treated in an atmosphere containing phosphorus to form a heavily phosphorus doped region 10 on the side of the upper surface of the film 9 and at the same time, the film 10 is flattened, a contact window 12 to reach a second conductivity type semiconductor layer 7 is opened by dry etching using a resist pattern 11 as a mask and the parts of the sidewalls of the window 12 are overetched by wet etching. Accordingly, the window 12 can be easily formed into a roughly forward-tapered form with an opening spread in the side of its upper surface.

COPYRIGHT: (C)1996,JPO

